



## EPSENT SYN - GEAR 75W-90

### DESCRIPTION

EPSENT SYN-GEAR 75W-90 is a fully synthetic lubricant based on carefully selected very high-quality base oils, which is recommended for the manual transmissions of most commercial vehicles. It is adapted to the requirements of synchromesh transmissions, procuring improved shift comfort, low temperature fluidity and longer service life.

### APPLICATIONS

EPSENT SYN-GEAR 75W-90 meets the requirements of many commercial vehicle builders and/or gearbox manufacturers, including DAF, IVECO, Eaton Europe, Renault (in accordance with B0032/2 Annex 3) and Volvo.

### BENEFITS:

- very smooth shift performance.
- significantly extended transmission life.
- excellent thermal and oxidation stability

### RECOMMENDATIONS / SPECIFICATIONS

**API** GL-4; **MAN** 341 E-3, 341 Z-4; **MB** 235.4; **RENAULT** B0032/2 Annex 3; **VOLVO** 97307, 97305; **ZF** TE-ML 01L ZF TE-ML 02L ZF TE-ML 08 ZF TE-ML 13 ZF TE-ML 16K ZF TE-ML 24A; Meets the requirements including DAF, IVECO, Eaton Europe, Volvo and Renault (in accordance with B0032/2 Annex 3)

*Always consult your manufacturer's handbook*

TYPICAL TECHNICAL PROPERTIES	
Product Code	701758
Density at 15°C, g/ml, ASTM D4052	0.870
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	120
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	15.9
Viscosity Index, ASTM D2270	140
Flash Point(COC), °C, ASTM D92	225
Pour Point, °C, ASTM D97	-42

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur