



## STEELCUT SOLUBLE 100

### DESCRIPTION

EPSENT STEELCUT SOLUBLE 100 is a long-life, bio stable, chlorine-free high-performance metal working fluid. When mixed with water the emulsion formed has a milky appearance. It is formulated with high levels of lubricity additives to provide excellent performance in arduous machining operations.

### PRODUCT FEATURES & BENEFITS

EPSENT STEELCUT SOLUBLE 100 is a high-performance, chlorine-free product suitable for machining a wide range of metals. It provides the flexibility for product rationalization and is particularly suitable for machining aluminum alloys used in the automotive industry. It is formulated to provide long service life and to resist bacterial growth to help reduce smells associated with bacterial degradation. Outstanding machining performance on aluminum, non-ferrous metals and ferrous metals, including stainless steels. Wide multi-metal machining range. Stable in a wide range of diluent water qualities. Oil content protects machined components, machine fittings and fixtures. Highly resistant to bacterial degradation

### APPLICATIONS

EPSENT STEELCUT SOLUBLE 100 is recommended for machining aluminum, steels and yellow metals. It can be used in individual machine sumps and in centralized coolant systems. Recommended dilutions for Turning, Drilling, Sawing, Milling, Reaming, Deep Hole Boring: 5-10%

### TYPICAL TECHNICAL PROPERTIES

Property	Value
Appearance	Amber Liquid
Specific Gravity @ 20°C	0.95
Emulsion Type	Milky
pH @ 3% Emulsion	9.4
Corrosion test (IP 287) Breakpoint %	4.0
Refractometer Correction Factor	1.0

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur